

2/19/31
DIALOG(R)File 347:JAPIO
(c) 2003 JPO & JAPIO. All rts. reserv.

04998586 **Image available**
LUBRICATING DEVICE OF COUNTER PROPELLER SHAFT SEAL DEVICE

PUB. NO.: 07-291186 [JP 7291186 A]
PUBLISHED: November 07, 1995 (19951107)
INVENTOR(s): EDA MASATOSHI
 OMURA TAKASHI
 TANAKA MASAHIRO
 AKATSU MASAMI
 UCHIYAMA KIYOSHI
APPLICANT(s): MITSUBISHI HEAVY IND LTD [000620] (A Japanese Company or
 Corporation), JP (Japan)
 EAGLE IND CO LTD [472011] (A Japanese Company or Corporation)
 , JP (Japan)
APPL. NO.: 06-107591 [JP 94107591]
FILED: April 22, 1994 (19940422)
INTL CLASS: [6] B63H-005/10; B63H-023/36; F16J-015/32
JAPIO CLASS: 26.3 (TRANSPORTATION -- Marine Vessels); 22.1 (MACHINERY --
 Machine Elements)

ABSTRACT

PURPOSE: To simplify the lubricating device of an inner shaft stern side shaft seal device (inner shaft rear part seal device) installed at the rear part of a front propeller, as for a counter propeller vessel.

CONSTITUTION: An inner **shaft** rear part **seal** device 7 is formed of a casing 7a installed at the rear end surface of a front propeller 5 (installed at the rear end part of an outer **shaft** 2) and the **lip** type seals 9-12 which are made of rubber and permit the slide contact between the inside diameter end part installed on the inner periphery of the easing 7a and a liner 8 on the inner **shaft** 1. Further, an emergency pipe 14 opened between the **lip** type seals 11 and 12 is laid on the inner surface of the outer **shaft** 2, and the end part of the pipe 14 is allowed to communicate to the lubricating oil chamber 3a of an outer **shaft** bearing 3 through a valve 15 and an oil hole 20 which penetrates in the longitudinal direction through a liner 16 forming an outer **shaft** front part sealing device 10, and the part in the vicinity of the outer **shaft** front part **seal** device 19 can be made simple.

C:\Program Files\Dialog\DialogLink\Graphics\23.bmp

